

Fiber Optics Distribution Box

GP31-2P16D-1

Overview

This fiber optics distribution box terminates up to 2 fiber optic cables, offers spaces for splitters and up to 16 fusions, allocates 16 SC adapters and working under outdoor environments. It is a perfect cost-effective solution-provider in the FTTx networks.

Features

- ABS+PC material used ensures the body strong and light.
- Mechanical seal: good sealing, can repeat use. Protective level: IP65.
- Laying: outdoor wall-mounting and pole-mounting.
- FTTH products, passive optical points wiring special terminal box.
- The box body to scroll type structure, it has the function of guard against theft, large capacity function complete, easy to use.
- Can be installed 1:8 or 1:16 PLC splitter.
- Maximum for LC 32cores, for SC 16 cores.



Dimensions and Capability

Adapter Capacity	LC Duplex	SC Simplex
	32	16
Dimensions (W*H*D)	240mm*306mm*106mm	
Number of Cable Entrance	Max Diameter 14mm*Q2	
Number of Cable Exit	Up to 16 Drop Cables	
Weight	1.68 KG	
Optional Accessories	Adapters, Pigtails, Heat Shrink Tubes, Splice Tray, Optical Splitter	
Installation	Wall-Mounted or Pole-Mounting	



Operation Conditions

Temperature	-40°C -- 60°C
Humidity	95% above 40°C
Air Pressure	62kPa – 105kPa

Shipping Information

Package Contents	Fiber optics distribution box, 1 unit; Keys for lock, 2 keys; Wall mount accessories, 1 set
Package Dimensions(W*H*D)	325mm*240mm*118mm
Material	Carton box
Weight	2.5 KG
Lead Time	10-15 working days normally

Part Details



