

Fiber Optics Distribution Box

GP31-2P16E

Overview

LongXing GP31-2P16E is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box. It is a perfect cost-effective solution-provider in the FTTx networks.

Features

- ABS + PC material used ensures the body strong and light.
- Water-proof design for both indoor and outdoor uses.
- Easy installations: wall-mounted or poled-mounted.
- Protection Level: IP65.
- Accommodates both feeder cables and drop cables.
- Micro type PLC splitter installation, easy maintenance.
- Cables, pigtails, and patch cords are running through their own paths without disturbing each other. This structure enables easy maintenance.
- Distribution panel can be flipped up, feeder cable can be placed by expression port, easy for maintenance and installation.



Dimensions and Capability

Dimensions (H*W*D)	241mm*208mm*117mm
Weight	1.16KG
Adapter Capacity	16 SC
Number of Cable Entrance	Max diameter 18mm, up to 2 cables
Optional Accessories	Pole mount accessories

Operation Conditions

Temperature	-40°C -- 85°C
Humidity	85% at 30°C
Air Pressure	70kPa – 106kPa

Shipping Information

Package Contents of Each Set	Terminal box, 1 unit; 1 key; Wall mount accessories: 1 set
Package Dimensions(W*H*D)	650mm*465mm*310mm (10 sets each package)
Material	Carton box
Weight	16KG
Lead Time	10-15 working days normally



Part Details

