Splice Tray

ST-1D24A

Overview

Splice tray is used in optical distribution frame, distribution box, and splice closures, which is engineered for use with indoor or outdoor splice hardware with both loose tube and tight-buffered optical cable designs. The compact splice cassettes designed for simple, cost effective low and mid-sized fiber splicing applications. Each cassette is supplied with splice holders that secure and protect both fusion and mechanical splices; also the top cover is included.

Features

- ABS material used ensures the body strong and light
- The fusing distribution board of the unit box is double layer structure, integrating the fusing and distribution into one unity.
- 24-fiber high-density splice trays •
- Protect and manage heat shrink style spliced fibers
- Heat shrink splice holder and sleeves included •
- Clear cover allows viewing or inspection of fibers without having to remove cover •
- Use for single-mode or multimode fiber
- Durable injection-molded plastic trays and covers
- Longer bending radius for fiber, Easy operation of pigtails •
- Easily disposed for particular needs
- Suitable for ribbon or non-ribbon optical fiber cable





Dimensions and Capability	
Dimensions (W*H*D)	210mm*156mm*18mm
Capacity	24 cores
Optional Accessories	Heat Shrink Tubes, Heat Shrink Splice Holder
Max diameter of entry cable	14.0mm
Weight	0.175 KG





LongXing Telecom Anju Road, Beilun District, Ningbo, China

info@lxtelecom.com www.lxtelecom.com



LongXingTelecom +86 574 87908988 +86 574 87908188 Ver: 051115




Operation Conditions		
Temperature	-40℃ 55℃	
Sealing performance	Remain unchanged for72 hours on pressure 70kpa	
Air Pressure	70kPa – 106kPa	
Tensile Strength	>1000N	
Compressive Strength	Withstand 2000N/10Cm ² in 1min	

	 	4
Shinh		
Shippi		

Package Contents	Splice Tray Base with Splice Holder; Splice Tray Cover
Package Dimensions(W*H*D)	260mm*200mm*60mm
Material	Carton box
Weight	0.65 KG
Lead Time	10-15 working days normally

Part Details











LongXing Telecom LongXing Telecom Anju Road, Beilun District, Ningbo, China


info@lxtelecom.com www.lxtelecom.com

You Tube

LongXingTelecom +86 574 87908988 +86 574 87908188 Ver: 051115



Catalog Number



Ordering Example:

ST-1D24A-24-1-1-24 24 cores, 1 cover, 1 base tray, 24 fusion tubes

Note: *Cable diameter is 0.9mm.

If the required type of any item is not on the relevant list, please use "O" or "OO" as the red cells indicate, and kindly state the required type in the description of PO.



info@lxtelecom.com www.lxtelecom.com



LongXingTelecom +86 574 87908988 +86 574 87908188 Ver: 051115



3