

Optical Splitter PLC Cassette Type

OSP-H

Overview

This optical splitter use Planer Lightwave Circuit (PLC) technology for split ratio 2, 4, 8, 16, 32 and 64. The Optical Splitter is designed for cassette splitter type by standard of YD/T2000-2009, YD/T1117-2001. Optical splitter cassette type refers to the port 2.0 mm / 3.0mm slip-on fiber multichannel direct output with a plastic box packaging protection and easy to use. Application for FTTX network, LAN/WAN or CATV network.



Features

- Low Insertion loss
- Low PDL
- Compact Design
- Good channel-to-channel uniformity
- Wide Operating Wavelength: From 1260nm to 1650nm
- Wide Operating Temperature: From -40°C to 85°C
- High Reliability and Stability



Technical Specification 1×N Series

Parameters	1×4	1×8	1×16	1×32	1×64	1×64		
Operation Wavelength (nm)	1260 - 1650					1310 ± 40	1490 ± 10	1550 ± 40
Insertion Loss (dB)	≤ 7.4	≤ 10.7	≤ 13.9	≤ 17.2	≤ 21.5	≤ 20.1		
PDL	≤ 0.3	≤ 0.3	≤ 0.3	≤ 0.3	≤ 0.5	≤ 0.3		
Uniformity of I.L	≤ 0.8	≤ 1.0	≤ 1.4	≤ 1.6	≤ 2.0	≤ 1.6		
Return loss (dB)							≥ 55	
Directivity (dB)							≥ 55	
Working / Storage Temperature (°C)							-40 ~ + 85	



LongXing Telecom
Anju Road, Beilun District, Ningbo, China
info@lxtelecom.com
www.lxtelecom.com



LongXing Telecom



LongXingTelecom



+86 574 87908988
+86 574 87908188
Ver: 240915

LONGXING

Structured Cabling Solutions

Technical Specification 2×N Series

Parameters	2×4	2×8	2×16	2×32	2×64	2×64	
Operation Wavelength (nm)	1260 - 1650					1310 ± 40	1490 ± 10 1550 ± 40
Insertion Loss (dB)	≤ 7.6	≤ 11.0	≤ 14.8	≤ 17.9	≤ 21.5	≤ 20.1	
PDL	≤ 0.3	≤ 0.3	≤ 0.3	≤ 0.3	≤ 0.3	≤ 0.5	
Uniformity of I.L	≤ 0.8	≤ 1.0	≤ 1.4	≤ 1.4	≤ 1.6	≤ 2.0	
Return Loss (dB)	≥ 55						
Directivity (dB)	≥ 55						
Working / Storage Temperature (°C)	-40 ~ + 85						

Operation Conditions

Temperature	-40°C -- 85°C
Humidity	93% at 40°C
Air Pressure	62kPa – 101kPa

Shipping Information

Package Contents	Optical Splitter PLC Mini Type 1 unit
Package Dimensions(W*H*D)	It depends on the dimensions of the product.
Material	Plastic Box
Weight	It depends on the weight of the product.
Lead Time	10-15 working days normally



LongXing Telecom



Anju Road, Beilun District, Ningbo, China



info@lxtelecom.com



www.lxtelecom.com



LongXing Telecom



LongXingTelecom



+86 574 87908988

+86 574 87908188

Ver: 250615

LONGXING

Structured Cabling Solutions

Part Details



Ratio: 1×2 1×4 2×4 1×8 2×8..

Dimension: 100×80×10 (L×W×D mm)..

Connector Options: FC SC..

Pigtail Diameter: Φ 2.0 mm / Φ 3.0 mm ..



Ratio: 1×16 2×16 1×32 2×32..

Dimension: 120×80×18 (L×W×D mm) ..

Connector Options: FC SC..

Pigtail Diameter: Φ 2.0 mm / Φ 3.0 mm ..



Ratio: 1×64 2×64..


Dimension: 141×115×18 (L×W×D mm)..

Connector Options: FC SC..

Pigtail Diameter: Φ 2.0 mm / Φ 3.0 mm ..



Catalog Number

OSPH - 

Parameters
A = 1 x 2
B = 1 x 4
C = 1 x 8
D = 1 x 16
E = 1 x 32
F = 1 x 64
G = 2 x 4
H = 2 x 8
I = 2 x 16
J = 2 x 32
K = 2 x 64
O = Other*

Connector Type
SU = SC UPC
SA = SC APC
FU = FC UPC
FA = FC APC
OO = Other*
NN = No requirement

Cable Length
Enter the length required
N = No requirement

Cable Diameter
C = 2.0mm
D = 3.0mm
O = Other*

Fiber Type
1 = G657
O = Other*

Ordering Example:

OSPH - ASU1C10 1 x 2, SC UPC, G657, 2.0mm Cable, 10m Cable.

Note : *If the required type of any item is not on the relevant list, please use "O" or "OO" as the red cells indicate, and kindly state the required type in the description of PO.

