

Fiber Optic Splice Closure

GPJ83 - D04

Overview

LongXing GPJ83-D04 fiber optic splice closures (FOSC) are used to distribute, splice, and store the outdoor optical cables which enter and exit from the ends of the closure. There are two connection ways: direct connection and splitting connection. Applicable to situations such as overhead, man-well of pipeline, embedded situation etc.

Features

- The protection grade reaches IP 68.
- Aerial and wall-mounting.
- Ambient temperature ranges from -40 to 65°C.
- The closure is of small volume, big capacity and convenient maintenance.
- The closure casing is made of quality engineering plastics, and of good performance of anti-erosion against acid and alkali salt, anti-aging, as well as smooth appearance and reliable mechanical structure.
- The mechanical structure is reliable and has the performance of resisting wild environment and intensive climate changes and serious working environment.
- The splice trays (FOST) inside the closure are turn-able like booklets, and have adequate curvature radius and space for winding optical fiber to make sure the curvature radius for optical winding 40 mm. Each optical cable and fiber can be operated individually.



Dimensions and Capacity

Outside Dimensions (Height*Diameter)	480mm*220mm
Weight (excluding outside box)	3500g - 4100g
Number of Inlet / Outlet Ports	6 pieces
Diameter of Fiber Cable	Φ5mm - Φ18mm
Capacity of FOSC	Bunchy: 12 cores - 288 cores; Ribbon: up to 432 cores

Main Components

Name of Components	Quantity	Usage	Remarks
FOSC Cover	1 piece	Protecting fiber cable splices in whole	Height*Diameter: 400*220 (mm)
Splice Tray (FOST)	Max. 6 trays (bunchy or ribbon)	Fixing heat shrink protective sleeve and holding fibers	Bunchy: 24, 36, 48, 72 cores Ribbon: 12, 18 pieces
Base	1 set	Fixing internal and external structure	N/A
Fiber Holding Tray	1 piece	Holding fibers with protective coat	N/A
Plastic Hoop	1 set	Fixing between FOSC cover and base	N/A
Gasket ring	1 set	Big gasket ring is used to seal FOSC cover and base. Small gasket ring is used to seal entry/exit tube	1 piece of big gasket ring, 6 pieces of small gasket ring
Pressure Testing Valve	1 set	After inject air, it is used for pressure testing and sealing testing	Configuration as per requirement.
Earthing Deriving Device	1 set	Deriving metallic parts of fiber cables in FOSC for earthing connection	Configuration as per requirement.



LongXing Telecom
Anju Road, Beilun District, Ningbo, China
info@lxtelecom.com
www.lxtelecom.com



LongXing Telecom



LongXingTelecom
+86 574 87908988
+86 574 87908188
Ver: 010816

LONGXING

Structured Cabling Solutions

Main Accessories and Special Tools

Name of Components	Quantity	Usage	Remarks
Heat Shrink Protective Sleeve	N/A	Protecting fiber splices	Configuration as per capacity
Nylon Tie	N/A	Fixing fiber with protective coat	Configuration as per capacity
Earthing Wire	1 piece	Putting through between earthing devices	N/A
Abrasive cloth	1 piece	Scratching fiber cables	N/A
Labeling Paper	1 piece	Labeling fibers	N/A
Special Wrench	2 piece	Installing and tightening nut of reinforced core and nut (plastic) of entry/exit tube	N/A
Measuring Paper	1 piece	To measure perimeter of fiber cable, of which the diameter is enlarged with seal tape	N/A
Seal Tape	1 ring	Enlarging diameter of fiber cable which fits in with gasket ring.	Configuration as per specification
Insulation Tape	1 ring	Enlarging diameter of fiber cable for easy fixing	N/A
Metal Hoop	1 set	For wall mounting and pole hugging	N/A
Buffer Tube	Customized	Hitched to fibers and fixed with FOST, managing buffer	Configuration as per requirement
Desiccant	1 bag	Put into FOSC before sealing for desiccating air	N/A

Necessary Tools for Installation

Supplementary Materials (to be provided by operator)

Name of Materials	Usage
Scotch Tape	Labeling, temporarily fixing
Ethyl Alcohol	Cleaning
Gauze	Cleaning

Special Tools (to be provided by operator)

Name of Tools	Usage
Fiber Cutter	Cutting off fibers
Fiber Stripper	Strip off protective coat of fiber cable
Combo Tools	Assembling FOSC

Universal Tools (to be provided by operator)

Name of Tools	Usage and Specification
Band tape	Measuring fiber cable
Pipe cutter	Cutting fiber cable
Electrical cutter	Take off protective coat of fiber cable
Combination pliers	Cutting off reinforced core
Screwdriver	Crossing/Paralleling screwdriver
Scissor	N/A
Waterproof cover	Waterproof, dust-proof
Metal wrench	Tightening nut of reinforced core

Splicing and Testing Instruments (to be provided by operator)


Name of instruments	Usage and Specification
Fusion Splicing Machine	Fiber splicing
OT DR	Splicing testing
Provisional splicing tools	Provisional testing

Shipping Information

Specification	Carton Size	Capacity	Net Weight	Remarks
Inner Box	220mm*215mm*490mm	1 pc	3.4kg - 4.0kg	Configuration as per weight
Outer Box	695mm*440mm*520mm	6 pcs	20.4kg - 24kg	Configuration as per weight

Notice: The above-mentioned tools and testing instruments should be provided by the operators themselves.


Part Details



Packing



Catalog Number



Ordering Example:

GPJ83-D04-B288: Bunchy pigtail, 288 cores.

Note : *If the required type of any item is not on the relevant list, please use "O" or "OO" as the red cells indicate, and kindly state the required type in the description of PO.

More relevant designs for your reference.

Model	Dimensions (L*W*H) / (H*Dia) mm	Capacity (Cores)		Number of Inlet/Out Ports	Cable Diameter (mm)
		Bunchy	Ribbon		
GPJ83-H01	390*210*120	12—96	72—144	3 pieces on each side (total 6 pieces)	Φ5—Φ16
GPJ83-H02	320*210*85	12—96	up to 144	6 pieces	Φ5—Φ20
GPJ83-H03	280*200*90	12—96	up to 144	max. 4 pieces	Φ5—Φ20
GPJ83-H04	450*220*110	12—192	72—288	3 (pieces) on each side (total 6 pieces)	Φ5—Φ23
GPJ83-H05	450*220*160	12—192	72—288	3 pieces on each side (total 6 pieces)	Φ5—Φ23
GPJ83-H06	395*195*130	12—96	72—144	3 pieces on each side (total 6 pieces)	Φ5—Φ20
GPJ83-H07	470*180*125	12—96	up to 144	3 (pieces) on each side (total 6 pieces)	Φ5—Φ20
GPJ83-H08	340*150*70	12—48	36—72	2 pieces on each side (total 4 pieces)	Φ5—Φ16
GPJ83-D01	430*190	12—96	up to 288	4 pieces	Φ5—Φ18
GPJ83-D02	540*205	24—96	up to 288	5 pieces	Φ5—Φ36
GPJ83-D03	420*190	12—96	up to 144	5 pieces	Φ5—Φ25
GPJ83-D04	480*220	12—288	up to 432	6 pieces	Φ5—Φ18
GPJ83-D05	310*190	12—48	up to 72	4 pieces	Φ5—Φ17
GPJ83-D06	460*190	12—96	up to 144	4 pieces	Φ8—Φ16
GPJ83-D07	310*190	12-48	N/A	4 pieces	Φ5—Φ25