

Rack Mount Patch Panel

ODU-L8 (2nd Generation)

Overview

This rack mount fiber patch panel is designed to fit on a standard 19" rack or optical fiber distribution frames, and provide optimal protection for your fiber optic applications. There are two cable entry points on the back of the fiber housing fitted with rubber grommets to protect the fiber optic cable from damage. Upon on customer's request, it can being loaded up to 48 connections, each fiber enclosure includes one cable routing spool and 24 fiber splice tray. LongXing's standard technical specifications are listed below; customer/special requirements are welcomed.



Features

- 2nd Generation: Open design of cable exits for easier access and maintenance.
- Top quality steel with electrostatic painted ensures the strong body and pleasing appearance.
- Easy installations: 19", 21" and 23" wall mounting.
- Easy operations: Drawer style.
- Cable inlet system provided on the rear side which has excellent performances for fixing outdoor cables.
- Fully stable patch panel, no risk of movement.
- Adoptable adapter types: FC, SC, LC.
- Options of Splice trays & fiber management guides.
- Protected patch panel offers secure environment for adapters, patch cords and pigtails.



Dimensions and Capability

| Height | Depth | Width | Capacity | |
|--------|-------|-------------|----------|-----------|
| | | | FC/SC/ST | LC duplex |
| 1U | 300 | 19"/21"/23" | 24 | 48 |
| 2U | 300 | 19"/21"/23" | 48 | 96 |
| 3U | 300 | 19"/21"/23" | 72 | 144 |
| 4U | 300 | 19"/21"/23" | 96 | 192 |

* Other height options available upon request.



LongXing Telecom
Anju Road, Beilun District, Ningbo, China
info@lxtelecom.com
www.lxtelecom.com



LongXing Telecom



LongXing Telecom



+86 574 87908988
+86 574 87908188
Ver: 060120

LONGXING

We Shape Solutions


Operation Conditions

| | |
|--------------|----------------|
| Temperature | -5°C -- 60°C |
| Humidity | 90% at 30°C |
| Air Pressure | 70kPa – 106kPa |

Shipping Information

| | |
|---------------------------|---|
| Package Contents | Patch panel, 1 unit |
| Package Dimensions(W*H*D) | It depends on the dimensions of the product |
| Material | Carton box |
| Weight | It depends on the dimensions of the product |
| Lead Time | 10-15 working days normally |

Part Details



LongXing Telecom

Anju Road, Beilun District, Ningbo, China

info@lxtelecom.com

www.lxtelecom.com



LongXing Telecom



LongXingTelecom



+86 574 87908988



+86 574 87908188

Ver: 060120

LONGXING

We Shape Solutions

Catalog Number

ODU-L8



| Material |
|---------------------|
| M = Metal |
| S = Stainless steel |
| O = Other* |

| Fusion Tube |
|-------------|
| Y = Yes |
| N = No |

| Capacity |
|-----------------------------|
| Enter the capacity required |

| Cable Color |
|--------------------|
| Y = Yellow |
| B = Blue |
| W = White |
| O = Orange |
| G = Green |
| Z = Brown |
| S = Slate |
| R = Red |
| H = Black |
| P = Purple |
| F = Rose |
| A = Aqua |
| C = Color coded |
| N = No requirement |

| ODU Color |
|------------|
| W = White |
| B = Black |
| G = Grey |
| O = Other* |

| Pigtail Quantity |
|-----------------------------|
| Enter the quantity required |
| N = No requirement |

| Height |
|------------|
| 1 = 1U |
| 2 = 2U |
| 3 = 3U |
| 4 = 4U |
| O = Other* |

| Connector Type |
|----------------------|
| SU = SC UPC |
| SA = SC APC |
| FU = FC UPC |
| FA = FC APC |
| LU = LC UPC (duplex) |
| LA = LC APC (duplex) |
| OO = Other* |

| Fiber Type | |
|----------------------|-------------|
| S = G652D | Single Mode |
| D = G655 | |
| K = G656 | |
| P = G657A1 | |
| L = G657A2 | Multi Mode |
| B = OM1 (62.5/125µm) | |
| G = OM1 (50/125µm) | |
| Q = OM2 (50/125µm) | |
| W = Om3 | |
| Y = Om4 | |
| O = Other* | |
| N = No requirement | |

| Adapter Quantity |
|-----------------------------|
| Enter the quantity required |
| N = No requirement |

Ordering Example:

ODU-L8M4W2SU4S4YN Metal, Four cores, White ODU, 2U, SC UPC, 4 Adapters, G652D, 4 Pigtails, Yellow cable, No fusion tube

Note: *If the required type of any item is not on the relevant list, please use "O" or "OO" as the red cells indicate, and kindly state the required type in the description of PO.