Rack Mount Patch Panel

ODU-L4

Overview

ODU-L4 rack mount patch panel can be installed on standard 19", 21" and 23" racks and currently being widely used in LongXing's optical fiber distribution frames. LongXing supplies top quality optical fiber distribution frame with very competitive prices, every single module is tested in the workshop before delivering to our customers. LongXing's standard technical specifications are listed below; Customer/special requirements are welcomed.



Features

- Removable front door with designation labels.
- Top quality steel with cover by electrostatic painted ensures the strong body and pleasing appearance.
- Easy operations: Drawer-type
- Easy installations: 19", 21" and 23" wall mounting.
- For standard 19", 21" and 23" racks use (other rack width options available on request).
- Fully stable patch panel, no risk of movement.
- Multi-functions Works with all LongXing Series A modules (not just for splicing & terminating, also with options for splitters or fiber storage).
- Protected patch panel offers secure environment for adapters, patch cords and pigtails.
- Adoptable adapter types: FC, SC, ST simplex adapters and LC duplex adapters.



Dimensions and Capability								
Height	Depth(mm)	Width	Module A1			Module A3		
			Capacity		Module	Capacity	Module	
			FC/SC/ST	LC duplex	Capacity	FC/SC	Capacity	
1U	300	19"/21"/23"	12	24	1	24	1	
2U	300	19"/21"/23"	24	48	2	48	2	
3U	300	19"/21"/23"	36	72	3	72	3	
			48	96	4	96	4	
4U	300	19"/21"/23"	60	120	5	120	5	
			72	144	6	144	6	

^{*} Height is upon request.









www.lxtelecom.com

Operation Conditions				
Temperature	-5°C 60°C			
Humidity	90% at 30℃			
Air Pressure	70kPa – 106kPa			

Shipping Information				
Package Contents	Patch panel, 1 unit			
Package Dimensions(W*H*D)	It depends on the dimensions of the product			
Material	Carton box			
Weight	It depends on the dimensions of the product			
Lead Time	10-15 working days normally			

Part Details




















Catalog Number



Ordering Example:

ODU-L4M4W2SU4S4YN Metal, Four cores, White ODU, 2U, SC UPC, 4 Adapters, G652D, 4 Pigtails, Yellow cable, No fusion tube

Note: "If the required type of any item is not on the relevant list, please use "O" or "OO" as the red cells indicate, and kindly state the required type in the description of PO.









