

Optical Fiber Distribution Frame

GPX09P



Dimensions and Capability

Dimensions(H*W*D)	Capacity(Core / Unit)	Max Unit	Max Capacity
2000*840*300	144	4	576
2200*840*300	144	5	720
2600*900*300	144	6	864

*Customized designs are available upon request



Overview

LongXing optical fiber distribution frame GPX09P is made of top quality steel and deformed aluminum alloy and treated with galvanizing, oxidation and electrostatic plastic spraying. The frame has solid structure and pleasing appearance.

Features

- This frame is made of top quality steel and deformed aluminum alloy and treated with galvanizing, oxidation and electrostatic plastic spraying.
- The frame has solid structure and pleasing appearance.
- The indoor frame contains the functions of optical fiber terminal, distribution, transfer and storage, with the advantage of big capacity, convenient for operation, as well as plays a major role in optical cable communications.
- Fully front side operation.
- Adapters are installed on the 12 cores splice and distribution integrated tray, as well as the tray is installed on the tray rack mount. (Capacity subjects to different requirements)
- Cable and pigtail can be inlet from the top of the frame. Cable (fiber) inlet hole is protected by cable-protected belt and contains enough space for fiber crossing.
- Both left and right sides of the frame are embedded removable structure, as well as the side rack should be removed when frames combine.



Optional Elements

- Hardware to fasteners, and fastening to the number of fiber needed can be offered on request.
- Elements to protect buffers depending on the number of cables needed can be offered on request.
- Accessories such as screws, nut, fasteners for raiser floor or concrete floor can be offered on request.
- Customer's logo can be printed on the upper left corner or upper right corner of the frame on request.

Operation Conditions

Temperature	-5℃ -- 60℃
Humidity	90% at 30℃
Air Pressure	70kPa – 106kPa

Shipping Information

Package Contents	ODF 1 unit
Package Dimensions(W*H*D)	It depends on the dimensions of the product
Material	wooden box
Weight	It depends on the dimensions of the product
Lead Time	10-15 working days normally



Catalog Number

GPX09P -

--	--	--	--	--	--	--	--	--	--

Dimensions
1 = 2000*840*300
2 = 2200*840*300
3 = 2600*840*300
O = Other*

Material
C = Cold-rolled Steel
S = Stainless Steel

ODF Color
W = White
B = Black
G = Gray
O = Other*

Patch Panel Type
1 = 144

Patch Panel Quantity
Enter the quantity required
N = No requirement

Cable Inlet
Y = Yes
N = No

Protection Tubes Length
Enter the length required
N = No requirement

Cable Entry
T = Top
B = Bottom
M = Both top and bottom

Ordering Example:

GPX09P-1CW1-4TNN 2000*840*300,Cold-rolled steel, White, 144 Cores patch panel, 4 Patch panels, Top cable entry, No protection tubes, No cable inlet.

Note : *If the required type of any item is not on the relevant list, please use "O" or "OO" as the red cells indicate, and kindly state the required type in the description of PO.

