

# Fiber Optics Distribution Box

GP31-1P02E

## Overview

LongXing GP31-1P02E optical distribution box terminates one fiber optic cable with up to 2 cores, connecting the drop cable and ONU devices through fiber port. It brings significant improvements resulting in better customer experience when FTTH have to be deployed.

## Features

- ABS+PC material used ensures the body strong and light.
- Easy installations: Mount on wall or just put on the ground.
- Splicing tray can be removed when needed or during the installation for the convenient operation and installation;
- Adapter slots adopted – No screws needed for installing adapters.
- Plug fiber with no need to open the shell, easily accessible fiber operation.
- Double-layer design for easier installation and maintenances:
  - ◇ Upper layer for splicing.
  - ◇ Lower layer for distribution.



Dimensions and Capability	
Dimensions (L*W*H)	100mm x 80mm x 22mm
Adapter Capacity	2 fibers with SC adapters
Number of Cable Entrance/Exit	3/2
Capacity	Up to 2 cores
Installation	Wall Mounted
Pigtail	G652D $\Phi$ 0.9mm, 0.5m or as per request
Optional Accessories	Adapters, Pigtails
Weight	0.16 KG



## Operation Conditions

Temperature	-5℃ -- 60℃
Humidity	90% at 30℃
Air Pressure	70kPa – 106kPa

## Shipping Information

Package Contents	Distribution box, 1 unit; Wall mount installation accessories, 1 set
Package Dimensions(W*H*D)	20pcs, 250mm×220mm×100mm
Material	Carton box
Weight	0.65kg
Lead Time	10-15 working days normally

## Part Details

