

Fiber Optic Patch Cord

MTP/MPO Trunk Cable

Overview

MTP/MPO is the industry acronym for multi-fiber push on. LongXing's new MTP/MPO connector offers up to 24 times the density of standard connectors, providing significant space and cost savings. MTP/MPO Connectors utilize precision molded MT Ferrules, with metal guide pins and precise housing dimensions to ensure fiber alignment when mating.



Features

- Color coded connector housings are available to differentiate fiber type as follows:
 - Green for SM
 - Yellow for SM Super Low loss
 - Beige for MM
 - Aqua for OM3 Fiber
 - Heather-Violet for OM4 Fiber
- Capacity are available in 4, 8, 12 and 24.
- Ferrules are available for SM Standard, SM Super Low Loss, MM Standard and MM Low Loss.
- Boots are available for Ribbon Cable, Ribbon Fiber and Round boot.



Highlights

- Lower Insertion loss
- Removable Housing
- Spring Push with Slit for easier assembly
- MTP/MPO-HD for High Density Application
- Flex angle boot and other boot styles
- IP-MTP/MPO Outdoor rated IP-68 housing



Applications

- Telecommunications
- Local area network
- Fiber to the home
- Testing instruments




Technical Specifications				
SPECIFICATION	SM STANDARD		MM STANDARD	
	Typical	Max	Typical	Max
MPO				
Insertion Loss	0.2 dB	0.7 dB	0.15 dB	0.50 dB
Return Loss	60 dB (8° Polish)		25 dB (Flat Polish)	
Durability	<0.30dB change 500 matings		<0.20dB change 1000 matings	
Ferrule type available	4, 8, 12, 24		4, 8, 12, 24	
Operating Temperature	-40 to +75°C			
Storage Temperature	-40 to +85°C			

Wire map configurations


Straight Type A wiring (Straight Through)		Total flipped Type B wiring (Cross)		Pair flipped Type C wiring (Cross Pair)	
Fiber	Fiber	Fiber	Fiber	Fiber	Fiber
1	1	1	12	1	2
2	2	2	11	2	1
3	3	3	10	3	4
4	4	4	9	4	3
5	5	5	8	5	6
6	6	6	7	6	5
7	7	7	6	7	8
8	8	8	5	8	7
9	9	9	4	9	10
10	10	10	3	10	9
11	11	11	2	11	12
12	12	12	1	12	11



Pre-terminated MTP Technology-Polarity



Catalog Number



Ordering Example:

J-MP-12-A-GR0N-0003-DB-000-F0/F0 MPO, 12 cord, Type A, 50/125μm OM3, Round cord, No fanout, 3 m, Patch cord, No fanout, Female type, flat polish, MPO/ Female type, flat polish, MPO.

Note: *If the required type of any item is not on the relevant list, please use "X", "XX", "XXX" or "XXXX" as the red cells indicate, and kindly state the required type in the description of PO.