

# FTTH Fiber Reservation Box

GP31-2P02A

## Overview

The GP31-2P02A FTTH Fiber Reservation Box provides a compact solution for connecting OSP fiber drops to customer distribution fibers via fusion splicing or SC/LC adapters. Preloaded with 30 meters of connectorized fiber on a rotating reel, it ensures fast, efficient FTTH deployment.



## Features

- PC+ABS material used ensures the body strong and light.
- Protective door designed for dust-proof.
- Sealing ring designed for water-proof.
- Easy installations: Ready for wall mount - installation kits provided.
- Cable fixing units provided for fixing optical cable.
- Removable cable entrance.
- Bend radius protected and cable routing paths provided.
- 30 meters long fiber optic cable can be coiled.
- Easy operation: no extra key is needed for closing
- Optional drop cable exit available on the top, side and bottom.



## Dimensions and Capability

Dimensions (W*H*D)	206mm*166mm*78.5mm
Optional Accessories	Fiber optical cable, adapter
Weight	0.46 KG
Adapter Capacity	1
Number of Cable Entrance/Exit	Max Diameter 3mm, up to 2 cables
Max Length of Cable	30m
Adapter Type	SC simplex, LC duplex



LongXing Telecom  
Anju Road, Beilun District, Ningbo, China  
info@lxtelecom.com  
www.lxtelecom.com



LongXing Telecom



LongXingTelecom



+86 574 87908988  
+86 574 87908188  
Ver: 010923

**LONGXING**

Structured Cabling Solutions

## Operation Conditions

Temperature	-40~+85℃
Humidity	93% at 40℃
Air Pressure	62kPa – 101kPa

## Product Details



## Shipping Information

Package Contents	Reservation box, 30 units/carton; Wall mount installation accessories, 30 sets/carton
Package Dimensions(W*H*D)	610mm*480mm*455mm
Material	Carton box
Weight	14.5 KG
Lead Time	10-15 working days normally

